# Driving towards a green future

### SOL APOLLO Series Smart AC EV Chargers





# Fully charged and ready!



# Reliable, powerful & easy to use

# Smart solutions for a greener future

The world's energy production and consumption is undeniably changing. The electrification of the mobility industry is contributing to this great change through the development and research of electric vehicles and related products at a global scale.

At Solplanet we know that every small conscious decision builds up to an environmentally sustainable future, that's why we are proud to present our new electric vehicle charger series, carefully designed applying over 15 years of our experience in the PV industry.

Every detail of our EV Chargers aims to bring the best possible experience for customers. Our intelligent monitoring system and user-friendly app allows you to control the whole charging process on your mobile device. Our SOL APOLLO EV Charger Series is fully compatible with your photovoltaic installation, allowing you to charge your vehicle directly using the power of the sun.

### You can depend on Solplanet

Solplanet is a brand of AISWEI, we've been manufacturing inverters since 2007. Our mother brand, also formerly known as SMA's Chinese subsidiary, has successfully been manufacturing high-quality and reliable products for renowned brands like SMA since 2017 and Zeversolar since 2013. Today, AISWEI is an independent research, development and manufacturing company. A recent equity restructuring puts us on particularly strong financial footing within the industry.

By launching our versatile and reliable Solplanet EV chargers, which can harness the power generated by our Solplanet inverters, we are taking a new step into becoming a key contributor to the global e-mobility revolution.

solplanet.net



Solplanet's new generation of AC EV chargers bring the latest technologies to your home for a safe and smart charging experience, with an elegant and easy-to-use design and adaptable functions that meet the needs of a wide range of user scenarios.

This new generation of AC EV Chargers come as a result of dedicated research, design and development based on our deep knowledge in the field of photovoltaic technology for over 15 years. The possibility of using solar energy in the charging process of your electric vehicle, comes not only with great economic benefits, but as a smart and environmentally conscious choice to living a greener life.

The SOL APOLLO Series provide several options for you to discover the best charging experience possible. Get ready, the green future is here!

# **Everything** you expect and more!



Innovative design

- · Elegant design with a dynamic and robust streamlined body
- By leveraging high tech paint technology, the sleek and aesthetically pleasing EV charger blends perfectly with both your EV and home
- Replaceable front cover for convenient substitution and additional color options



#### Safe

- TÜV IEC 61851-1 & CE compliant
- Integrated Type A RCD, 30mA AC and 6mA DC leakage protection
- Built-in PEN fault detection without extra earth rods
- Type 2 socket with shutter (opt.)
- Dynamic load balancing (opt)



#### Smart & Eco-friendly

- Standard wireless communication via WIFI / Bluetooth. 4G (opt.)
- Intelligent Ai-Charging App for remote control and monitoring
- Scheduled charging and off-peak charging modes
- Adjustable charging power (6A to 32A)
- Lock / unlock the charger via APP
- Solar charging under Solar PV & Eco Mode (opt.)
- Recyclable packaging





#### Easy-to-install

- Compact, lightweight and wall mountable
- Easy-to-install with standard tools
- Toolless plug in terminal blocks
- Quick set-up via Bluetooth and APP
- Cable entry on the front or rear of the housing

Γ Ω\_ (IK10)

#### Reliable

- IP65 enclosure suitable for outdoor use
- IK10 protection rating
- Exterior & interior covers for multiple protection
- 3 years standard warranty



#### User-friendly

- RFID & NFC for user authentication
- Integrated NFC technology, unique authentication via smartphone
- Cable Holster housing design
- Ergonomic plug handles
- LED status indicators
- Wireless firmware updates
- Automatic phase detection and balancing (3 phase series)

Series: SOL7.4H

SOL11H SOL22H

## **SOL APOLLO** Series

Solplan Solplane

Technical Datasheet

## 7.4 kW Single Phase

Cable Version

	1			
Input & Output	Rated Voltage	230 V ac		
	Rated Frequency	50 Hz / 60 Hz		
	Max. Output Power	7.4 kW		
	Max. Output Current	32	32 A	
	Standby Power Consumption	2 W		
	Residual Current Detection	Type A: AC 30 mA / DC 6 mA		
	Connector Type (IEC62196-2)	Туре 2	Type 2 Type 2 socket <sup>1,2</sup>	
	Cable Length	5 m / 7.5 m	-	
	Network Interface	WIFI & Bluetooth & RS485 & LAN <sup>3</sup>		
	RFID/NFC Reader	•		
ace	Status Indication	LED Light strip		
rol	Built-in 4G	0		
User Interface & Control	Smart APP	•		
S C Se	Communication Protocol	OCPP1.6J		
	Protection	IP65 (Enclosure)		
	Operating Temperature	-25°C to 50°C		
Jt	Storage Temperature	-40°C to 70°C		
Working Environment	Relative Humidity	Non-condensing		
rkin	Altitude	Up to 2000 m		
Env	Cooling Concept	Natural Convection		
	Impact Protection Class	IK	IK10	
	UV Resistant	•		
	Mounting	Wall		
	Dimensions (W/H/D)	230 / 360 / 130 mm		
cal.	Weight	6 kg	2.5 kg	
Mechanical	Colour	Morandi B	<ul> <li>Morandi Blue /          Black     </li> </ul>	
Mec	Cable Holder	•	_	
ety	DC Leakage Protection	•		
	Over Temperature Protection	٠		
	Ground Protection	•		
	Surge Protection (EN60664)	• (Type III)		
Safety	Certification	RoHS, CE, TUV / EN/IEC 61851-1		
	1			

• Standard features / O optional features / – not available 1) Self-closing cover and built in electronic lock is standard / 2) Shutter for cover is optional / 3) LAN is optional Optional smart meter for solar charging function and dynamic load balancing Version: March 2022

#### Socket Version

#### **Technical Datasheet**

## 11 kW Three Phase

Technical Datasheet

## 22 kW Three Phase

Cable Version

	Rated Voltage	400 V ac	
	Rated Frequency	50 Hz / 60 Hz	
	Max. Output Power	11 kW	
	Max. Output Current	16 A	
put	Standby Power Consumption	2 W	
Input & Output	Residual Current Detection	Type A: AC 30 mA / DC 6 mA	
ut &	Connector Type (IEC62196-2)	Type 2 Type 2 socket <sup>1,2</sup>	
Inpi	Cable Length	5 m / 7.5 m	_
	Network Interface	WIFI & Bluetooth & RS485 & LAN <sup>3</sup>	
	RFID/NFC Reader	•	
CO	Status Indication	LED Light strip	
rol rol	Built-in 4G	0	
User Interface & Control	Smart APP	•	
S O S O	Communication Protocol	OCPP1.6J	
	Protection	IP65 (Enclosure)	
	Operating Temperature	-25°C to 50°C	
t	Storage Temperature	-40°C to 70°C	
Working Environment	Relative Humidity	Non-condensing	
iror	Altitude	Up to 2000 m	
ы М М	Cooling Concept	Natural Convection	
	Impact Protection Class	IK10	
	UV Resistant	•	
	Mounting	Wall	
	Dimensions (W/H/D)	230 / 360 / 130 mm	
Ca	Weight	6 kg	2.5 kg
hanical	Colour	● Morandi Blue / ● Black	
Mec	Cable Holder	•	-
	DC Leakage Protection	•	
	Over Temperature Protection	•	
Safety	Ground Protection	•	
	Surge Protection (EN60664)	• (Type III)	
	Certification	RoHS, CE, TUV / EN/IEC 61851-1	

Cable Version

Socket Version

Input & Output	Rated Voltage	400 V ac			
	Rated Frequency	50 Hz / 60 Hz			
	Max. Output Power	22 kW			
	Max. Output Current	32 A			
	Standby Power Consumption	2 W			
	Residual Current Detection	Type A: AC 30 mA / DC 6 mA			
	Connector Type (IEC62196-2)	Туре 2	Type 2 Type 2 socket <sup>1,2</sup>		
	Cable Length	5 m / 7.5 m	-		
	Network Interface	WIFI & Bluetooth & RS485 & LAN <sup>3</sup>			
	RFID/NFC Reader	•			
ace	Status Indication	LED Light strip			
User Interface & Control	Built-in 4G	C	0		
	Smart APP	•			
S O S	Communication Protocol	OCPP1.6J			
	Protection	IP65 (En	IP65 (Enclosure)		
	Operating Temperature	-25°C t	-25°C to 50°C		
int	Storage Temperature	-40°C	-40°C to 70°C		
Working Environment	Relative Humidity	Non-condensing			
viro	Altitude	Up to 2000 m			
ŠЕ	Cooling Concept	Natural C	Natural Convection		
	Impact Protection Class	IK	IK10		
	UV Resistant	•			
	Mounting	W	Wall		
	Dimensions (W/H/D)	230 / 360	230 / 360 / 130 mm		
a	Weight	6 kg	2.5 kg		
echanical	Colour	Morandi B	● Morandi Blue / ● Black		
Mec	Cable holder	•	-		
	DC Leakage Protection	•			
	Over Temperature Protection	•	•		
Safety	Ground Protection	•			
	Surge Protection (EN60664)	• (Ty	• (Type III)		
	Certification	RoHS, CE, TUV / EN/IEC 61851-1			

• Standard features / O optional features / – not available 1) Self-closing cover and built in electronic lock is standard / 2) Shutter for cover is optional / 3) LAN is optional Optional smart meter for solar charging function and dynamic load balancing Version: March 2022

#### Socket Version

Smart EV Charger monitoring system

## Ai-Charging App

Our state-of-the-art Ai-Charging App allows you to manage, configure and control your charger remotely from your mobile device. Full control in the palm of your hand!

Our designers have created from scratch an incredible tool: With an elegant and user-friendly interface. We, at Solplanet are driven by the idea of making things easy for installers and end-users alike, we've developed this App after thoroughly researching the habits and needs of our users.

## Join us for a fully charged drive towards a green future!

### Features

- Multiple wireless control solutions: Standard wireless communication via WIFI or Bluetooth. 4G (opt.)
- Charging history: Understand your personal charging habits through a graphical interface, to optimize your experience
- Scheduled charging sessions: Manage your charging times and save costs by using off-peak electricity rates or your own solar energy production.

- Security: Instantly lock and unlock your charger through your mobile device
- Shared management: Easy-to-use configuration to grant shared management access to your family or community
- Upgrade service: Compatible with a smart-meter, allowing you to take advantage of solar charging and dynamic load balancing feature





## Easy and smart charging experience.

# Harness the power of the sun

At Solplanet we strive to create the best possible experience for distributors, installers and end users. That's why our products are easy-to-install, reliable and user-friendly.

<u> </u>	Easy-to-install	<ul> <li>Quick &amp; easy-to-install with standard tools</li> <li>Quick setup and commissioning with AISWEI apps</li> <li>Compact wall mount design</li> </ul>
	Reliable	<ul> <li>International quality standards</li> <li>Integrated DC switch</li> <li>IP65 rated design for outdoor use</li> </ul>
	User-friendly	<ul> <li>User-friendly app interface</li> <li>Online monitoring via Wi-Fi and AISWEI apps</li> <li>Award winning inverter design</li> </ul>



### Explore our product catalogue

We offer a variety of high-quality products designed to cover your needs, no matter the size of your installation. Our deep experience in the PV industry and the manufacturing of solar inverters allows us to provide highly reliable interconnectable equipment. With this new SOL APOLLO EV Charger series, we give a new step to a greener future.



Single phase string inverters



Three phase string inverters



Hybrid

inverters



### Contact your local office:

SOLPLANET INTERNATIONAL info@solplanet.net sales@solplanet.net service@solplanet.net www.solplanet.net

SOLPLANET AUSTRALIA & NEW ZEALAND Sales: +61 390 988 674 sales.au@solplanet.net Service: +61 390 988 674 service.au@solplanet.net

SOLPLANET BRAZIL Sales: +55 51 99765 3389 sales.br@solplanet.net Service: +55 0800 606 6016 service.br@solplanet.net SOLPLANET GERMANY Sales: +49 151 59184325 sales.de@solplanet.net Service: +31 20 800 4844 (EN) service.eu@solplanet.net

SOLPLANET HUNGARY Sales: +36 70 787 00 70 sales.hu@solplanet.net Service: +36 465 00 384 service.hu@solplanet.net

SOLPLANET POLAND Sales: +48 600 080 311 sales.pl@solplanet.net Service: +48 134 926 109 service.pl@solplanet.net SOLPLANET SPAIN Sales: +34 676 633 900 sales.es@solplanet.net Service: +31 20 800 4844 (EN) service.eu@solplanet.net

SOLPLANET THE NETHERLANDS Sales: +31 202 402 557 sales.nl@solplanet.net Service: +31 20 800 4844 (EN) service.eu@solplanet.net

SOLPLANET TURKEY Sales: +90 554 631 1089 sales.tr@solplanet.net Service: +90 850 346 0024 service.tr@solplanet.net

AISWEI GREATER CHINA Sales:+86 512 6937 2978 sales.china@aiswei-tech.com Service: +86 400 801 9996 service.china@aiswei-tech.com



### solplanet.net